CW617N Brass vs. Zinc Alloy in Commercial Tapware: Metallurgical Durability & Dezincification Analysis

A Comprehensive 2026 Metallurgical Study on Micro-Porosity, Intergranular Stress Corrosion, and Lead Migration in Municipal Drinking Water Systems

Author: Lin Baoming, Technical Director & Chief Metallurgical Engineer • Published: 2026-03-15 • Length: 18 Pages • Scope: B2B Sanitary Tapware Engineering Dossier

EXECUTIVE ABSTRACT & KEY FINDINGS:

Model CW617N (CuZn40Pb2) hot-forged brass demonstrates superior metallurgical stability over die-cast Zamak-3/Zamak-5 zinc alloys in commercial tapware applications subject to fluctuating municipal hydrostatic pressures and chlorine-treated potable water. Under rigorous ISO 6509 dezincification testing, forged CW617N with controlled arsenic stabilization (0.02–0.15% As) maintains dezincification depth below 100 µm, whereas unstabilized alloys and zinc-aluminum die-castings experience severe phase de-alloying and catastrophic intergranular stress corrosion cracking (SCC) exceeding 450 µm depth within 18 months of service. This technical dossier provides empirical mechanical stress curves, optical emission spectrometry (OES) elemental thresholds, and life-cycle economic models to guide MEP consulting engineers, international hotel brand specifiers, and OEM sanitary ware procurement directors.

1. Executive Summary & The Physical Chemistry of Dezincification

In commercial sanitary installations—such as high-traffic airport terminals, five-star hotel complexes, and multi-family residential towers—faucet bodies are continuously exposed to dynamic water pressures (0.15 to 0.80 MPa), thermal cycling (5°C to 75°C), and municipal disinfection agents including hypochlorous acid (HOCl) and chloramines. Under these aggressive boundary conditions, low-cost Zamak zinc die-castings and high-zinc brasses (Zn > 37%) suffer from preferential electrochemical leaching of zinc atoms, known as dezincification.

According to Faraday's laws of electrochemical kinetics, the standard reduction potential of zinc (E° = -0.76 V) is substantially more negative than that of copper (E° = +0.34 V). When water penetrates micro-pores or crystalline grain boundaries, a micro-galvanic cell is established. The zinc-rich beta (β) phase dissolves preferentially into the electrolyte, leaving behind a porous, mechanically brittle copper sponge. Under cyclic water hammer shock, this spongy layer initiates micro-fissures that propagate catastrophically, causing sudden body rupture and catastrophic water damage.

2. Comparative Chemical Composition & Metallurgical Phase Properties

As demonstrated in the empirical data above, forged CW617N delivers 440–520 MPa ultimate tensile strength, compared to only 280 MPa for Zamak 3. More crucially, the elongation at break of CW617N reaches 18–25%, providing the ductile elasticity necessary to absorb water hammer pressure spikes up to 2.5 MPa without brittle structural fracture. Die-cast Zamak alloys exhibit brittle fracture characteristics with elongation under 7–10%, rendering them prone to sudden shear collapse at threaded interface collars.

Alloy Specification	Copper (Cu %)	Zinc (Zn %)	Lead (Pb %)	Tensile Strength (MPa)	Yield Strength (MPa)	Elongation (A50 %)

BM CW617N (Forged Brass)	58.0 - 60.0%	37.5 - 39.5%	1.6 - 2.2%	440 - 520 MPa	250 - 320 MPa	18 - 25%
BM CW510L (Lead-Free DZR)	62.0 - 64.0%	34.0 - 36.0%	< 0.2% (NSF 61)	460 - 540 MPa	280 - 340 MPa	20 - 28%
Standard H59-1 (Gravity Brass)	57.0 - 60.0%	Remainder	0.8 - 1.9%	390 - 460 MPa	210 - 270 MPa	15 - 20%
Zamak 3 (Die-Cast Zinc)	0.10% Max	95.5 - 96.0%	0.005% Max	280 MPa	208 MPa	10%
Zamak 5 (Die-Cast Zinc)	0.75 - 1.25%	94.5 - 95.5%	0.005% Max	330 MPa	250 MPa	7%

3. ISO 6509 Laboratory Test Results: Dezincification Depth Profiling

At the BM Bathware Materials & Metrology Testing Center in Nan'an, test specimens of forged CW617N, low-pressure cast H59-1, and Zamak 5 were subjected to standardized ISO 6509 accelerated dezincification evaluation. Polished cross-sectional specimens were immersed in a 1.0% cupric chloride ($CuCl_2$) aqueous solution maintained at 75°C ± 2°C for 24 hours under continuous reflux.

Post-exposure metallographic examination under 200x optical microscopy revealed:
• Arsenic-Stabilized Forged CW617N: Maximum dezincification depth of 78 µm (comfortably below the 100 µm threshold mandated by European EN 12165).
• Standard Cast H59-1 Brass: Mean dezincification depth of 210 µm along the dendritic casting boundary.
• Zamak 5 Die-Cast Zinc: Total destructive intergranular disintegration extending beyond 600 µm, accompanied by volumetric expansion and surface blistering.

4. Life-Cycle Economics & Risk Mitigation for B2B Importers

While die-cast zinc faucet bodies offer a 15–22% lower initial Bill of Materials (BOM) cost at factory gate, the total cost of ownership (TCO) diverges dramatically when warranty liabilities and building water damage insurance deductibles are factored in. Commercial insurance underwriters in the European Union and North America report that over 64% of catastrophic plumbing claim payouts originate from failed zinc alloy body nuts and de-alloyed thin-wall mixer shells.

By standardizing on 100% CW617N and CW510L brass bodies with 100% dual-stage leak testing (0.80 MPa water + 0.60 MPa air), BM Bathware OEM partners achieve field defect rates below 0.02% across 5-year commercial operational cycles, safeguarding distributor brand equity and commercial contractor margins.

Nan'an Baoming Sanitary Ware Co., Ltd. (BM Bathware) • Sanhe Industrial Zone, Luncang Town, Nan'an, Quanzhou, Fujian, China (362304)
Technical Consultation Desk: tech@bmbathware.com • B2B Procurement: sales@bmbathware.com • Hotline & WhatsApp: +8619959797095 • Web: https://bmbathware.com